



RoHS Compliance



Material:

Housing: 30% Glass Filled PPS UL94V-0

Contacts: Beryllium Copper Or Phosphor Bronze

Plating: Gold 1.25u" Over 50u" Nickel

Electrical Characteristics:

Current Rating : 3.0AMP

Insulator Resistance: 1000MΩ min. at 100V AC

Contact Resistance: 10mΩ max.

Operating Temperature: -40°C ~ +105°C

Order Information:

RHTAY09E-1-XX-S-Z

IC Socket

ROW

1-Single Layer

2-Double Layer

XX-No. of 01~80 Pins

Straight Pin:

S=17.8mm S2=14.3mm

Material:

Y-Imported Beryllium Copper


Z-Domestic Phosphor Bronze

RHTECP NINGBO RHT ELECTRONIC CO.,LTD




UNITS:mm	SHEET SIZE: A4	SCALE:----	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5

CHK'D BY FENG
APPR BY ZHAN

2.54mm Pitch SIP Socket Connector	
THIRD ANGLE PROJECTION	RHTAY09E-1-XX-S-Z



RoHS Compliance



Material:

Housing: 30% Glass Filled PPS UL94V-0

Contacts: Beryllium Copper Or Phosphor Bronze

Plating: Gold 1.25u" Over 50u" Nickel

Electrical Characteristics:

Current Rating : 3.0AMP

Insulator Resistance: 1000MΩ min. at 100V AC

Contact Resistance: 10mΩ max.

Operating Temperature: -40°C ~ +105°C

Order Information:

RHTAY09E-1-XX-S2-Z

IC Socket

ROW

1-Single Layer

2-Double Layer

XX-No. of 01~80 Pins

Straight Pin:

S=17.8mm S2=14.3mm

Material:

Y-Imported Beryllium Copper

Z-Domestic Phosphor Bronze




RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5

CHK'D BY FENG
APPR BY ZHAN

2.54mm Pitch SIP Socket Connector
THIRD ANGLE PROJECTION
RHTAY09E-1-XX-S2-Z

RoHS Compliance



Material:

Housing:30% Glass Filled PPS UL94V-0

Contacts:Beryllium Copper Or Phosphor Bronze

Plating: Gold 1.25u" Over 50u" Nickel

Electrical Characteristics:

Current Rating :3.0AMP

Insulator Resistance:1000MΩ min.at 100V AC

Contact Resistance:10mΩ max.

Operating Temperature:-40°C~+105°C

Order Information:

RHTAY09E-2-XX-S-Z

IC Socket

ROW

1-Single Layer

2-Double Layer

XX-No.of 01~80 Pins

Straight Pin:

S=17.8mm S2=14.3mm

Material:

Y-Imported Beryllium Copper


Z-Domestic Phosphor Bronze

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4		SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN




2.54mm Pitch SIP Socket Connector

THIRD ANGLE PROJECTION



RHTAY09E-2-XX-S-Z

RoHS Compliance




Material:
 Housing: 30% Glass Filled PPS UL94V-0
 Contacts: Beryllium Copper Or Phosphor Bronze
 Plating: Gold 1.25u" Over 50u" Nickel

Electrical Characteristics:
 Current Rating : 3.0AMP
 Insulator Resistance: 1000MΩ min. at 100V AC
 Contact Resistance: 10mΩ max.
 Operating Temperature: -40°C ~ +105°C




Order Information:
RHTAY09E-2-XX-S2-Z

IC Socket
 ROW
 1-Single Layer
 2-Double Layer
 XX-No. of 01~80 Pins
 Straight Pin:
 S=17.8mm S2=14.3mm
 Material:
 Y-Imported Beryllium Copper
 Z-Domestic Phosphor Bronze

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN	2.54mm Pitch SIP Socket Connector	
0~3	3~18	18~50	50~120	CHK'D BY FENG	THIRD ANGLE PROJECTION 
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	

 NINGBO RHT ELECTRONIC CO.,LTD


RoHS Compliance



Material:
 Housing:30% Glass Filled PPS UL94V-0
 Contacts:Beryllium Copper Or Phosphor Bronze
 Plating: Gold 1.25u" Over 50u" Nickel

Electrical Characteristics:
 Current Rating :3.0AMP
 Insulator Resistance:1000MΩ min.at 100V AC
 Contact Resistance:10mΩ max.
 Operating Temperature:-40°C~+105°C

Order Information:
 RHTAY09EA-1-XX-S1-Y




Material:
 Y-Imported Beryllium Copper
 Z-Domestic Phosphor Bronze






NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4				SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	2.54mm Pitch SIP Socket Connector	
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	THIRD ANGLE PROJECTION	RHTAY09EA-1-XX-S1-Y



RHTAY09EA-1-XX-S1-Y

RoHS Compliance



Material:

Housing:30% Glass Filled PPS UL94V-0

Contacts:Beryllium Copper Or Phosphor Bronze

Plating: Gold 1.25u" Over 50u" Nickel

Electrical Characteristics:

Current Rating :3.0AMP

Insulator Resistance:1000MΩ min.at 100V AC

Contact Resistance:10mΩ max.

Operating Temperature:-40°C~+105°C

Order Information:

RHTAY09EA-2-XX-S1-Y

IC Socket

ROW

1-Single Layer

2-Double Layer

XX-No.of 01~80 Pins

Straight Pin:S1=9.2mm

S2=10.2mm S3=11.2mm S4=12.2mm

S5=13.2mm S6=14.2mm S7=14.2mm

Material:

Y-Imported Beryllium Copper

Z-Domestic Phosphor Bronze

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5

CHK'D BY FENG
APPR BY ZHAN

2.54mm Pitch SIP Socket Connector
THIRD ANGLE PROJECTION
RHTAY09EA-2-XX-S1-Y