


RECOMMENDED PCB LAYOUT
TOL±0.05



Material

Housing:Hing Temperature Thermoplastic,
UL94V-0 LCP,Black
Contact:Copper Alloy C5191
Shell:Copper Alloy C2680

Finish:

Contact:Plated Gold In Mating Area;Tin On Solder Talls
Shell:Nickel Plating

Electrical:

Current Rating:1.0A/Contact Terminal.
Voltage Rating:30V DC
Contact Resistance:50mΩ Max.
Dielectric Withstanding Voltage:300 V AC AT Sea Level.
Insulation Resistance: 100MΩ Min.
Connector Mate And Unmated Force
Mate Force:3.0kgf Max.
Unmated Force:0.7kgf Min.
Terminal Retention:0.5kgf Min

Order Information

RHTAY244-B-R

Micro USB
Color:B-Black
R-Reel Packing


 NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5

CHK'D BY FENG
APPR BY ZHAN

CONN RCPT 5POS MICRO USB SMD

THIRD ANGLE PROJECTION



RHTAY244-B-R