



Note:

- 1: V.S.W.R:1.5(0~3G), Max.
- 2: Wire surface shall have no dirt, broken.
- 3: Connector surface with coating, oxidation phenomenon.
- 4: Connector pins and insulator are in the same plane

Order Information

RHTAYFCA05 - OD1.13 - L300 - X

Wire Color:Not-Black
G-Gray BR-Brown

Lengs:L300=300mm

Cable OD0.81-0.81mm RF Cable
OD1.13-1.13mm RF Cable
OD1.32-1.32mm RF Cable
OD1.37-1.37mm RF Cable
RG178-RG178 RF Cable
RG316-RG316 RF Cable

Series:I-PEX To RP SMA Jack Female

7	CAP	Rubber CAP.Red	PCS	1
6	Nut	T1.8mm Nut,1/436UNS-2A	PCS	1
5	Washers	T0.4mm Washers	PCS	1
4	Connector	SMA Jack,Female Straight,for RG178,RG316,0.81,1.13, 1.32,1.37mm	PCS	1
3	RF Cable	RG178,RG316,0.81,1.13,1.32,1.37mm Cable	mm	L
2	Heat-Shrink Tube	ø1.0mm Heat-Shrink Tube,Block,L15mm	PCS	2
1	Connector	I-PEX Plug,for RG178,RG316,0.81, 1.13, 1.32,1.37mm Cable	PCS	1
No.	Name	Description	UNITS	Q'ty

NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4				SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	I-PEX to SMA Female Cable	
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	THIRD ANGLE PROJECTION	RHTAYFCA05-XXXX

