




Technical Parameters:
 Rated Voltage:DC 30V
 Rated Current: 0.5 A
 Contact Resistance:0.03Ω,Max
 Insulation Resistance:100MΩ,Min
 Pressure:AC500V(50Hz)/1minute
 Insertion Force:2-20 N
 Life: 50000 Times
 Operating Temperature:-30℃~70℃
 Material:
 WASHER :IRON
 HOUSING :PA66
 CURVE PIECE/NUT : C2680
 CONTACT FOOT/SPRING : C5191



T:1.6 Dimensions Of PC Board Holes
 Tolerance:±0.1(Printed-Top View)

SCHEMATIC					
004D	004DA	004DB	004DC	004DD	004DE

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL:±0.3

ORDER INFORMATION
 RHTAYG6.3-004DA

6.3mm Stereo Jack Series
 Schematic See Annex

NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5
			CHK'D BY FENG
			APPR BY ZHAN

Stereo Jack Series	
THIRD ANGLE PROJECTION	RHTAYG6.3-004DA