


Material:  
Housing:High Temperature  
Thermoplastic,UL94V-0,Black.  
Terminal:Copper Alloy.Contact Au;G.FPlating  
Shell:Stainless Steel.Slider Plating  
Au:1u",Ni:30u" Min.  
Electrical:  
Current Rating:1.0A  
Rating Voltage:50V  
Contact Resistance:100mΩ Max.  
Insulation Resistance:1000mΩ Min./500V DC  
Dielectric Withstanding Voltage:500V AC  
Solder ability:255±5 °C,5+5S  
Humidity:80% R.H. Max.  
Durability:5000 Cycles Min.  
Operating condition: Temperature-40°C +85°C

 NINGBO RHT ELECTRONIC CO.,LTD

|          |                |       |        |               |                                                                                                                                     |                                                    |  |
|----------|----------------|-------|--------|---------------|-------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------|--|
| UNITS:mm | SHEET SIZE: A4 |       |        | SCALE:---     | DRWN BY PAN                                                                                                                         | Micro SIM CONN;PUSH/PUSH,8Pin H3.65mm, with CD Pin |  |
| 0~3      | 3~18           | 18~50 | 50~120 | CHK'D BY FENG | THIRD ANGLE PROJECTION<br> RHTAYIM-096-H3.65-R |                                                    |  |
| ±0.12    | ±0.15          | ±0.3  | ±0.5   | APPR BY ZHAN  |                                                                                                                                     |                                                    |  |