



1 2 3 4 5 6 7 8 9


A




B



C



Recommended PCB Layout



SECTION A-A

Material and other:

Housing: PA66, UL94V-0

Pin Header: Brass, Tin Plated

Wire Guard: Stainless steel

Contact Resistance: 20mΩ Max

Insulation Resistance: 500MΩ/DC500V


Stripping Length: 10mm

Temp. Range: -40°C+105°C

MAX Soldering: 250°C±5°C for 5S

Order Information

RHTBY43R-7.62-XXP-X



Terminal Block

Pitch: 7.62mm

No. of (1~XX) Pins

Color: 1=Gray 2=Blue 3=Black

4=Green 5=Orange 6=Red

7=Transp 8=Yellow 9=White

Electrical Characteristics	UL	IEC
Rated Voltage	300V	250V
Rated Current	10A	15A
Withstand Voltage	AC2000V/1min	---
Wire Range	22~16 AWG	1.0mm ²



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4			SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	

7.62 Spring Terminal Blocks



RHTBY43R-7.62-XXP-X

1 2 3 4 5 6 7 8 9