



#### Material

Housing: PA66, UL94V-0

Screw: M2 Steel, Zn plated

Clamp: Brass, Ni Plated

Cage: Brass, Ni plated

Fix screws: M2.5 Steel, Zn plated

#### Electrical

Rated voltage: 300V

Rated current: 8A

Wire range: 28~16AWG 1.5mm<sup>2</sup>

Contact Resistance: 20 mΩ

Insulation resistance: 500MΩ/DC500V

Withstand voltage: AC2000V/1min

#### Mechanical

Temp. Range: -40℃~+105℃

Strip length: 6~7mm

Torque: 0.2Nm (1.7 bin)

#### Order Information

RHTBYDGFM-3.81-XXP-4 S XX

Terminal Block

Pitch

No. of Pole

Color: 4-Green

Screw: S-Slot Screw

C-Cross Screw

Product Code: 00~99



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm

SHEET SIZE: A4

SCALE:---

DRWN BY PAN

0~3

3~18

18~50

50~120

CHK'D BY FENG

±0.12

±0.15

±0.3

±0.5

APPR BY ZHAN

Pluggable Terminal Block 3.81 MM

THIRD ANGLE PROJECTION



RHTBYDGFM-3.81-4S-00