

#### Electrical :

Rated voltage: 300V

Rated current: 8A

Contact resistance: 20mΩ

Insulation resistance: 5000MΩ/1000V

Withstanding Voltage: AC2000V/1Min

#### Material

Pin header: Brass, Tin plated

Housing: PA66, UL94V-0

#### Mechanical

Temp. Range: -40°C~+105°C

MAX Soldering: +250°C for 5 Sec

#### ORDER INFORMATION

Product NO.: RHTBYDKF-3.81-XXP X X X

Series No. \_\_\_\_\_

Pitch: 3.81mm \_\_\_\_\_

Number of Pole \_\_\_\_\_

Color: 1=Gray 2=Blue 3=Black \_\_\_\_\_

4=Green 5=Orange 6=Red \_\_\_\_\_

7=Transparent 8=Yellow 9=White \_\_\_\_\_

Screw: C=Cross Screw \_\_\_\_\_

S=Slot Screw \_\_\_\_\_

Customer Request \_\_\_\_\_



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm

SHEET SIZE: A4

SCALE:---

DRWN BY PAN

Series Pitch= 3.81mm

0~3

3~18

18~50

50~120

CHK'D BY FENG

THIRD ANGLE PROJECTION

RHTBYDKF-3.81-XXPXXX


±0.12

±0.15

±0.3

±0.5

APPR BY ZHAN



1

2

3

4

5

6

7

8

9