




1 2 3 4 5 6 7 8 9

A



SECTION A-A



SECTION B-B

Material

Housing:PA66, UL94V-0

Screw:M3, Steel,Zinc plated

Pin header:Brass, Tin plated

Wire guard:Brass,Ni plated

Electrical

Rated voltage: 300V

Rated current: 15A

Wire range:28~14AWG 2.5mm²

Contact Resistance: 20mΩ

Insulation resistance: 500MΩ/DC500V

Withstand voltage:AC2000V/1min

Mechanical

Temp. Range:-40°C~+105°C

Step length:7 mm

Torque:0.4 Nm(3.6 Lb.in)

Order Information

RHTBYGKM-5.00-XXP-4 S XX

Terminal Block

Pitch_____

No.of Pole_____

Color:4-Green_____

Screw:S- Slot Screw_____

C-Cross Screw

Product Code: 00~99



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm

SHEET SIZE: A4

SCALE:---

DRWN BY PAN

Pluggable Terminal Block 5.00MM

0~3

3~18

18~50

50~120

CHK'D BY FENG

±0.12

±0.15

±0.3

±0.5

APPR BY ZHAN



RHTBYGKM-5.00-XXP-4S-00

1

2

3

4

5

6

7

8

9

A

B

C

D


E

F

G

1 2 3 4 5 6 7 8 9


A




B

Electrical Characteristics	UL	IEC
Rated Voltage	300V	250V
Rated Current	15A	12A
Withstand Voltage	1600/1min	4.0KV
Wire Range	28~12 AWG	0.2~2.5 mm ²

C



D



E

Material and other:
Housing:PA66,UL94V-0
Pin Header:Copper alloy,Sn Plated
Screw/Torque:Steel,M3/0.5Nm
Stripping Length:7~8mm
Operating temperature:-40°C~+105°C

Order Information

RHTBYGKM-5.08-XXP-X

Terminal Block

Pitch:5.08mm

No.:of(02~24)Pins


Color:1=Gray 2=Blue 3=Black

4=Green 5=Orange 6=Red

7=Transp 8=Yellow 9=White

Screw:SC=Slot/Cross

S-Slot Screw C-Cross Screw



Pitch 5.08mm Terminal Block

THIRD ANGLE PROJECTION

RHTBYGKM-5.08-XXP-XX



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm

SHEET SIZE: A4

SCALE:---

DRWN BY PAN

0~3

3~18

18~50

50~120

CHK'D BY FENG

±0.12

±0.15

±0.3

±0.5

APPR BY ZHAN

1

2

3

4

5

6

7

8

9

A

B

C

D

E

F

G