



1 2 3 4 5 6 7 8 9


A




B



C




D




SECTION A-A

E



F



RECOMMENDED PCB LAYOUT

Material

Housing:Hing Temperature Thermoplastic with g.f,UL94V-0,Black

Contact:Copper Alloy,t=0.20mm.

Shell:Copper Alloy,t=0.25mm.

Electrical:

Current Rating:1A Max.

Dielectric Withstanding Voltage:

100 V AC for 1min.

Contact Resistance:50mΩ Max.

Insulation Resistance:100mΩ Min.

Total Mating Force:3.57 kgf Max.

Total Unmating Force: 1.0 kgf Min.

Temperature Range: -30°C Up To +80°C

Order Information

RHTAY247-B-R

Micro USB

Color:B=Black

R-Reel Packing



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm

SHEET SIZE: A4

SCALE:---

DRWN BY PAN

CONN RCPT 5POS MICRO USB DIP 7.2mm

0~3

3~18

18~50

50~120

CHK'D BY FENG

±0.12

±0.15

±0.3

±0.5

APPR BY ZHAN

THIRD ANGLE PROJECTION



RHTAY247-B-R

1

2

3

4

5

6

7

8

9

A

B

C

D

E

F

G