

1	2	3	4	5	6	7	8	9
---	---	---	---	---	---	---	---	---

A

A

B

B

C

C

D

D

E





E

F

F

G

G



Material:

Housing:High Temperature Thermoplastic,
UL94V-0 LCP/PBT,Black/White.

Contact:Copper Alloy C2680

Shell:Copper Alloy C2680/SPCC

Finish:

Contact:Plated Gold In Mating Area:
Tin On Solder Tails
Shell:Nickel Plating

Electrical:

Current Rating:1.5A/Contact Terminal.

Voltage Rating:30V DC

Contact Resistance:30mΩ Max.

Dielectric Withstanding Voltage:
500 V AC AT Sea Level.

Insulation Resistance: 1000MΩ Min.

Connector Mate And Unmated Force

Mate Force:3.75kgf Max.

Unmated Force:1.02kgf Min.

Terminal Retention:1.2kgf Min

 NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm

SHEET SIZE: A4

SCALE:---

DRWN BY PAN

CONN PLUG MICRO USB
TYPE B Solder T3.0,L8.8mm

0~3

3~18

18~50

50~120

CHK'D BY FENG

±0.12

±0.15

±0.3

±0.5

APPR BY ZHAN



RHTAY35-2

1

2

3

4

5

6

7

8

9