



1 2 3 4 5 6 7 8 9


A




B




C




D



E



F



Material

Housing:CLP,UL94V-0

Shell:C2680/SPCC

Terminal:C2680

Electrical:

Current Rating:2A, Rated voltage:5V

Dielectric Withstanding Voltage:500 V AC for 1 min.

Contact Resistance:30mΩ Max.

Insulation Resistance:100MΩ Min.

Mechanical properties:

Total Mating Force:3.57 kgf Max.

Total Unmating Force:1.0 kgf Min.

Insertion force:5~20N,Pull-out force:5~20N

Life test:5000 cycles

Thrust force:50N min,Peel strength:150N min

Operation temperature:-20°C+85°C

Order Information

RHTAY37A-0-0-0-R

Micro USB

Post:1-With Post

0-Without Post

Terminal Plated:

0-Gold plated 1-Tin plated

Malar:

0-Without Mylar 1-With Mylar

Packing:T-Tube p-Tray

R-Tape on Reel



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm

SHEET SIZE: A4

SCALE:---

DRWN BY PAN

Micro 5P 6.4 USB Straight L=5.0

0~3

3~18

18~50

50~120

CHK'D BY FENG

±0.12

±0.15

±0.3

±0.5

APPR BY ZHAN



RHTAY37A-0-0-0-R

1

2

3

4

5

6

7

8

9

A

B

C

D

E

F

G