


SCHEMATIC LAYOUT



No Locking Pate
No Ground Link

Electrical Specification:

Contact Resistance: $\leq 0.03\Omega$

Insulation Resistance: $\geq 100m\Omega$

Withstand Voltage: 500V AC (50Hz)/minute

Rated Load: 50V DC, 1A

Insertion And Extraction Force: 4-40N

Temperature Range: -30°C to $+80^{\circ}\text{C}$

Order Information:

RHTAYLR-S02-03-F-R-L2.6

XLR Jack Series.

03=3PIN

F=Female

S=Dip Straight Pin

R=Dip Right Pin



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm

SHEET SIZE: A4

SCALE:---

DRWN BY PAN

XLR Socket

0~3

3~18

18~50

50~120

CHK'D BY FENG

THIRD ANGLE PROJECTION

RHTAYLR-S02-03-F-R-L2.6


± 0.12

± 0.15

± 0.3

± 0.5

APPR BY ZHAN



1

2

3

4




5

6

7

8

9



No Locking Pate
No Ground Link

Electrical Specification:
Contact Resistance: $\leq 0.03\Omega$
Insulation Resistance: $\geq 100m\Omega$
Withstand Voltage: 500V AC (50Hz)/minute
Rated Load: 50V DC, 1A
Insertion And Extraction Force: 4-40N
Temperature Range: -30°C to $+80^{\circ}\text{C}$

Order Information:
RHTAYLR-S02-03-F-S-L2.6

XLR Jack Series.

03=3PIN

F=Female

S=Dip Straight Pin

R=Dip Right Pin



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4		SCALE:---
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5

DRWN BY PAN

CHK'D BY FENG

APPR BY ZHAN

XLR Socket

THIRD ANGLE PROJECTION



RHTAYLR-S02-03-F-S-L2.6