

1

2

3

4

5

6

7

8

9

A

A

B

B

C

C

D

D

E




E

F


F

G

G



PCB Layout



Material:

Housing: PBT+Glass Filled Polyester

Flammability Rating: UL94V-0

Contacts: Phosphor Bronze Ø0.46mm

Plating: Gold Plating

Shield: Brass, Tin Plating

Electrical:

Voltage Rating: 125VAC

Current Rating: 1.5A

Contact Resistance: 30mΩ Max.

Insulation Resistance: 500MΩ Min.

Dielectric Strength: 1000VAC Rms 50Hz, 1 Min.

Durability: 600 cycles Min.

Operation Temperature: -40°C ~ +70°C

Order Information

RHTLY13-8P8C-2x1-X-G/Y-XX

Contacts: 8P8C

Shield Code: _____

1-with Shield

2-with EMI Shield

LED Code: LEFT/RIGHT

G/Y-Green/Yellow

Y/G-Yellow/Green

Plating Code: _____

01-1μ Gold Plating, 02-3μ Gold Plating

03-6μ Gold Plating, 04-15μ Gold Plating

05-30μ Gold Plating



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm

SHEET SIZE: A4

SCALE:---

DRWN BY PAN

0~3

3~18

18~50

50~120

CHK'D BY FENG

±0.12

±0.15

±0.3

±0.5

APPR BY ZHAN

Modular jacks RJ45-8P8C
2x1 Jack Shield with LED

RHTLY13-8P8C-2x1-X-X/X-XX

1

2

3

4

5

6

7

8

9