


Technical Parameters:
 Rated Voltage:DC 30V
 Rated Current: 0.5 A
 Contact Resistance:0.03Ω,Max
 Insulation Resistance:100MΩ,Min
 Pressure:AC500V(50Hz)/1minute
 Insertion Force:2-20 N
 Life: 50000 Times
 Operating Temperature:-30°C~70°C
 Material:
 Housing-A/B/Insulator/Pin Board :PBT
 Contact Clip:C5210R-EH AG CLAD
 Center Pin Material:
 Terminal 1,2,3:Copper Alloy
 Terminal 4,5,6,7,8,9:Brass
 Terminal 10,11,Bushing :Brass
 Spring:Stainless Steel



MODEL NO	005A	005AA	005AB	005AC	005AD	005AE
SCHEMATIC						

ORDER INFORMATION
 RHTAYSJ3.5-005A

3.5mm Dip Stereo Jack
 Schematic:See Annex

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5
CHK'D BY FENG		APPR BY ZHAN	

Dip Stereo Jack
 THIRD ANGLE PROJECTION
 RHTAYSJ3.5-005A