


Technical Parameters:
 Rated Voltage:DC 30V
 Rated Current: 0.5 A
 Contact Resistance:0.03Ω,Max
 Insulation Resistance:100MΩ,Min
 Pressure:AC500V(50Hz)/1minute
 Insertion Force:2~20 N
 Life: 50000 Times
 Operating Temperature:-30°C~70°C
 Material:
 Housing -A/B/INSULATOR/PIN BOARD:PA66
 Contact Clip: C5210r-EH AG CLAD
 Center Pin Material:
 Terminal 1,2,3 : Copper Alloy
 Terminal 4,5,6,7,8,9,10,11 : Brass



MODEL NO	005B	005BA	005BB	005BC	005BD	005BE
SCHEMATIC						

ORDER INFORMATION
 RHTAYSJ3.5-005BA
 3.5mm Dip Stereo Jack
 Schematic:See Annex

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5
			CHK'D BY FENG
			APPR BY ZHAN

Dip Stereo Jack
 THIRD ANGLE PROJECTION
 RHTAYSJ3.5-005B