



Technical Parameters:
 Rated Voltage:DC 30V
 Rated Current: 0.5 A
 Contact Resistance:0.03Ω,Max
 Insulation Resistance:100MΩ,Min
 Pressure:AC500V(50Hz)/1minute
 Insertion Force:2-20 N
 Life: 50000 Times
 Operating Temperature:-30°C~70°C
 Material:
 Housing Material:PBT
 Center Pin Material:
 Terminal 1 :Brass
 Terminal 2 :Copper Alloy
 Terminal 3 :Brass
 Bushing :Brass

MODEL NO	007B	007BA
D DIA	Without NUT Ø6.0	Without NUT Ø6.0
A	4.00mm	4.00mm
SCHEMATIC		

ORDER INFORMATION
 RHTAYSJ3.5-007B A

3.5mm Dip Stereo Jack
 A:With NUT B:Without NUT
 Schematic:See Annex

NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4			SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	

Dip Stereo Jack
 THIRD ANGLE PROJECTION

 RHTAYSJ3.5-007B