




1 2 3 4 5 6 7 8 9

A



MATERIAL

- 1.Housing: Nylon 66
- 2.Rocker: PC & PA66
- 3.Contacts: Silver Alloy
- 4.Terminal: Brass Silver Plated
- 5.Lamp: Neon Lamp,Tungsten Lamp
- 6.Spring: SWP,SUS
- 7.Movable Arm: Brass Silver Plated

ELECTRICAL

- 1.Electrical Rating:(G): 6(2)A 250VAC T125/55 1E4
10A 125VAC
(H):10(4)A 250VAC T125/55 1E4
10(2)A 250VAC T85/55 5E4
16A 125V/10A 250VAC 1/3HP 125-250VAC
- 2.Mechanical life: Over 30000 Cycles
- 3.Electrical life: Over 10000 Cycles
- 4.Contact Resistance:<20mΩ
- 5.Insulation Resistance:>1000MΩ
- 6.High Voltage Resistance:>1500V 1 min
- 7.Ambient Temperature: Terminal Side -20°C~+85°C;
Actuating Side -20°C~+55°C
- 8.Storage Temperature: -30°C~+80°C Max
- 9.Atmospheric Humidity: Max 85%
- 10.Actuating force: 4~8N(depends on different switch function)
- 11.Flammability: UL94V-2
- 12.Temperature rise at the terminal: Max 30°C (UL1054)
- 13.Solder ability of terminal: Max 350°C 3S

ORDER INFORMATION				
Series No.	RHTGY16-11	-G	-2	BK/BK
Function	11:ON-OFF 2P			-P8
Rating	G:10A 250VAC 6A 250VAC H:16A 125VAC 10A 250VAC			
Cap Printing	0: None 1: 2: 3:			
Color Cap/Housing	BK:Black WT:White RE:Red GE:Grey			
Terminal	P4 P8 			



NINGBO RHT ELECTRONIC CO.,LTD


UNITS:mm	SHEET SIZE: A4	SCALE:---	
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5

DRWN BY PAN

CHK'D BY FENG

APPR BY ZHAN

Rocker Switch Series



RHTGY16

1 2 3 4 5 6 7 8 9

A

B

C

D

E

F

G