




P.C.B LAYOUT



CIRCUIT

ELECTRICAL

Rating:0.3A 30V DC

Function:1P3T

Timing:Non-Shorting

Contact Resistance:80mΩ Max.

Insulation Resistance:100MΩ Min.at 500V DC

Dielectric Strength: AC 500V For 1Min

Operating Temper:-20°C~80°C

Operating Force:200±50gf

Life Test:10000 Cycles

Order Information:

RHTGYSS-1336-X-B

1P3T

STEM Color:

B-Black

PACKING:B-BAG

5	TERMINAL A/B/C	C2680	Ag PLATED	8
4	CONTACT	C5210	Ag PLATED	2
3	BOTTOM	PA66	Black	1
2	COVER	SUS	Natural	1
1	STEM	PA66	Black	1
NO.	PARTS	MATERIAL	FINISHING&COLOR	Q'TY



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm

SHEET SIZE: A4

SCALE:---

DRWN BY PAN

Mini Slide Switch,13.0x3.5x3.5mm,1P3T

0~3

3~18

18~50

50~120

CHK'D BY FENG

THIRD ANGLE PROJECTION

±0.12

±0.15

±0.3

±0.5

APPR BY ZHAN



RHTGYSS-1336