



Move Cover



US JACK  
6P4C Fu"



A-View




MATERIAL  
 HOUSING: ABS  
 CONTACT: PHOSPHOR BRONZE, HARD GOLD  
 SHIELDING: 0.25mm THICKNESS COPPER ALLOY WITH TIN PLATED  
 GOLD PLATING: 3u INCH, 6u INCH, 15u INCH, 30u INCH, 50u INCH  
 ELECTRICAL  
 CURRENT RATING: 1.5AMPS  
 VOLTAGE RATING: 125VAC  
 WITHSTANDING VOLTAGE: AC1000V RMS 50Hz or 60Hz 1Min  
 INSULATION RESISTANCE: 100MEG OHMS MIN  
 CONTACT RESISTANCE: 39MILLI OHMS MAX  
 WORKING TEMPERATURE : -35°C ~80°C

**RHTECP** NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4			SCALE:---
0~3	3~18	18~50	50~120	
±0.12	±0.15	±0.3	±0.5	

DRWN BY PAN  
 CHK'D BY FENG  
 APPR BY ZHAN

Modular Jack Connector  
 THIRD ANGLE PROJECTION  
  
 RHTLY87-6P4C