


Material:
 Housing: Polycarbonate, Transparent
 UL94V-0 Or UL94V-2
 Contacts: Brass, Gold Plating
 Shield: Brass T=0.25mm, Nickel Plating

Electric:
 Rated Current: 250 V AC, 2A
 Contact Resistance: 35mΩ Max.
 Insulation Resistance: 500MΩ Min, 100V DC/min
 Withstand voltage: 500V AC/1 minute
 No Breakdown

Mechanical:
 Durability: 500 Cycles Min.
 Operation Temperature: -40℃ ~ +85℃

Order Information
 RHTLYJ11B-4PxC-xx X

Point No. _____
 Gold Plating _____
 01-Fu*Gold Plating
 02-3u*Gold Plating
 03-6u*Gold Plating
 15-15u*Gold Plating
 30-30u*Gold Plating
 50-50u*Gold Plating
 Flammability: _____
 Blank-UL94V-2 0-UL94V-0



G	NINGBO RHT ELECTRONIC CO.,LTD			UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN	FTP CAT5E 4P4C Modular plugs, FLAT CABLE ENTRY WITH SHIELDED AND TWO SIDE LATCH		
					0~3	3~18	18~50	50~120	CHK'D BY FENG	THIRD ANGLE PROJECTION
					±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	
1	2	3	4	5	6	7	8	9		