



Material:  
Housing: Polycarbonate, Transparent  
UL94V-0 or UL94V-2  
Contacts: Brass, Gold Plating  
Electrical:  
Rated Current: 125V AC 1.5A@25°C  
Contact Resistance: 20mΩ Max.  
Insulation Resistance: 500MΩ Min. 100V DC/Min  
Withstand Voltage: 1000VAC/1 Minute  
No Breakdown  
Mechanical:  
Insertion Force: 30N Max  
Withdrawal Force: 30N Max.  
Durability: 750 Cycles Min.  
Operation Temperature: -40°C~+85°C

Order Information  
RHTLYJ12-6P6C-xx X X

Point No. \_\_\_\_\_  
Gold Plating \_\_\_\_\_  
01-1u"Gold Plating  
02-3u"Gold Plating  
03-6u"Gold Plating  
15-15u"Gold Plating  
30-30u"Gold Plating  
50-50u"Gold Plating  
BLADE Type: \_\_\_\_\_  
Flammability: \_\_\_\_\_  
Blank-UL94V-2 0-UL94V-0

G	NINGBO RHT ELECTRONIC CO.,LTD			UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN	UTP CAT3 6P6C RJ12 Modular Plugs	
			0~3	3~18	18~50	50~120	CHK'D BY FENG	THIRD ANGLE PROJECTION	
			±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	RHTLYJ12-6P6C-xxXX	
1	2	3	4	5	6	7	8	9	