

Type A



Type D

BLADE Type

Material:

Housing: Polycarbonate, Transparent

UL94V-0 Or UL94V-2

Contacts: Brass, Gold Plating

Shield: Brass T=0.25mm, Nickel Plating

Electrical:

Rated Current: 125V AC 1.5A@25°C

Contact Resistance: 20mΩ Max.

Insulation Resistance: 500MΩ Min. 100V DC/Min

Withstand Voltage: 1000VAC/1 Minute

No Breakdown

Mechanical:

Durability: 750 Cycles Min.

Operation Temperature: -40°C~+85°C

Order Information

RHTLYJ12B-6P6C-xx X X

Point No. _____

Gold Plating _____

01-Fu*Gold Plating

02-3u*Gold Plating

03-6u*Gold Plating

15-15u*Gold Plating

30-30u*Gold Plating

50-50u*Gold Plating

BLADE Type: _____

Flammability: _____

Blank-UL94V-2 0-UL94V-0

NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm

SHEET SIZE: A4

SCALE: ---

DRWN BY PAN

UTP CAT3 6P6C RJ12 Modular Plugs

0~3

3~18

18~50

50~120

CHK'D BY FENG

THIRD ANGLE PROJECTION


±0.12

±0.15

±0.3

±0.5

APPR BY ZHAN



RHTLYJ12B-6PxC-xxXX

1

2

3

4

5

6

7

8

9