

PCB LAYOUT/TOP VIEW

Electrical:

- 1.Voltage Rating: 125VAC
- 2.Current Rating: 1.5A
- 3.Contact Resistance: 30mΩ Max.
- 4.Insulation Resistance: 500MΩ Min.@500VDC
- 5.Withstanding Resistance: 1000VAC RMS, 50Hz 1minute

Materials:

- 1.Housing: Glass Filled Polyester, UL 94V-0
- 2.Contact: Phosphor Bronze T=0.35mm
- 3.Plating: Gold Plating over Nickel
FU", 3U", 6U", 15U", 30U", 50U"

Mechanical:

- 1.Durability: 750 cycles Min.
- 2.PCB Retention pre-solder: 1 LB Min.

Environmental:

- 1.Storage:-40°C~+85°C
- 2.Operation:-40°C~+85°C

Order Information:

RHTLYMT09-8P8C-W-XX-R

Point No: 8P8C

Shield Code:W-Without Shield

Plating: _____

01: Fu" Gold 02: 3u" Gold

03: 6u" Gold 04: 15u" Gold

05: 30u" Gold


Packing: R-Reel P-Blister Tray

NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4			SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	

RJ45-8P8C SMD Jack Horizontal,
With Shielded & Post

THIRD ANGLE PROJECTION



RHTLYMT09-8P8C-W-XX-R