



PCB LAYOUT/TOP VIEW

Notes :

MATERIALS

HOUSING: HIGH TEMP. THERMOPLASTIC FLAMMABILITY

UL94V-0

CONTACTS: PHOSPHOR BRONZE

PLATING: GOLD PLATING OVER NICKEL IN CONTACT

TIN PLATING OVER NICKEL IN SOLDER AREA

Electrical:

1.Voltage Rating: 125 Vac Rms

2.Current Rating: 1.5 Amp

3.Contact Resistance: 40 Milliohms Max

4.Insulation Resistance: 1000 Megohms Min@500 Vdc

5.Dielectric Strength: 1000 Vac Rms 60Hz,1Min

Mechanical:

1.Operating: 750 Cycles Min

Environmental:

1.Storage: -40°C To +85°C

2.Operation: -20°C To +75°C Gold Plating:6U'

Mates With Modular Plug Conforming To FCC Part 68,Subpart F

**RHTECP** NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4				SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	THIRD ANGLE PROJECTION	
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN		

RJ11-4P4C SMD Jack Horizontal

RHTLYMT22-4P4C-N-03-P