

Recommended PCB Layout Tolerance±0.05

Electrical:

- 1.Voltage Rating: 125VAC
- 2.Current Rating: 1.5A
- 3.Contact Resistance: 30mΩ Max.
- 4.Insulation Resistance: 500MΩ Min.@500VDC
- 5.Withstanding Resistance: 1000VAC RMS, 50Hz 1minute

Materials:

- 1.Housing: High Temp. Thermoplastic Flammability UL94V-0
- 2.Contact: Phosphor Bronze
- 3.Plating: Gold Plating over nickel in contact, Tin Plating over nickel in solder area
- 4.Shield: 0.23 Thickness Brass With Nickel Plated

Mechanical:

- 1.Durability: 750 cycles Min.
- 2.PCB Retention pre-solder: 1 LB Min.

Environmental:

- 1.Storage:-40°C~+85°C
- 2.Operation:-40°C~+75°C

Order Information:

RHTLYMT11-8P8C-W-Y/G-XX-R


- Point No: 8P8C
- Shield Code:W-Without Shield
- LED Code : Left/Right
- Y/G-Yellow/Green
- Plating:01: 1u" Gold 02: 3u" Gold
- 03:6u" Gold 04: 15u" Gold 05:30u" Gold
- Packing: R-Reel P-Blister Tray

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4			SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	

RJ45-8P8C SMD Jack Horizontal,
With Shielded&LED

THIRD ANGLE PROJECTION



RHTLYMT11-8P8C-W-Y/G-XX-R