



PCB Layout<Top View>

Electrical:

- 1.Voltage Rating: 125VAC
- 2.Current Rating: 1.5A
- 3.Contact Resistance: 40mΩ Max.
- 4.Insulation Resistance: 1000MΩ Min.@500VDC
- 5.Withstanding Resistance: 1000VAC RMS, 60Hz 1minute

Materials:

- 1.Housing: High Temp Thermoplastic Flammability,UL94V-0
- 2.Contact: Phosphor Bronze
- 3.Plating: Gold Plating Over Nickel In Contact
Tin Plating Over Nickel In Solder Area

Mechanical:

- 1.Durability: 750 cycles Min.

Environmental:

- 1.Storage:-40°C~+85°C
- 2.□peration:-20°C~+75°C

Order Information:

RHTLYMT13-4P4C-N-XX-P

Point No: 4P4C

Shield Code:N-Without Shield

Plating:

- 01: 1u" Gold 02: 3u" Gold
- 03: 6u" Gold 04: 15u" Gold
- 05: 30u" Gold

Packing: R-Reel P-Blister Tray

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4			SCALE:---
0~3	3~18	18~50	50~120	
±0.12	±0.15	±0.3	±0.5	

DRWN BY PAN
CHK'D BY FENG
APPR BY ZHAN

RJ11-4P4C SMD Jack Horizontal,
Without Shielded

THIRD ANGLE PROJECTION

RHTLYMT13-4P4C-N-XX-P