



Note:

- 1: V.S.W.R: 1.5(0~3G), Max.
- 2: Wire surface shall have no dirt, broken.
- 3: Connector surface with coating, oxidation phenomenon.
- 4: Connector pins and insulator are in the same plane

Order Information

RHTAYFCA02-RG174-L300

Series: SMA Female-MMCX Male
 Cable: RG174 Cable or RG316 Cable
 Lengs: L300=300mm

No.	Name	Description	UNITS	QTY
1	Connetor	MMCX Plug Straight, for RG174 or RG316	PCS	1
2	Heat-Shrink Tube	∅2.5mm Heat-Shrink Tube, Black, L15mm	PCS	2
3	RF Cable	RG174 Cable, Black, ∅∅2.7mm	mm	L
4	Connector	SMA Jack, Female Straight, for RG174, with CAP(Red)	PCS	1
5	Washers	T0.4mm Washers	PCS	1
6	Nut	T1.8mm Nut, 1/4 36UNS-2A	PCS	1

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4		SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN

SMA Female to MMCX Male Cable

THIRD ANGLE PROJECTION

RHTAYFCA02-XXXX