



Note:

- 1:V.S.W.R:1.5(0~3G),Max.
- 2:Wire surface shall have no dirt,broken.
- 3:Connector surface with coating,oxidation phenomenon.
- 4:Connector pins and insulator are in the same plane

Order Information

RHTAYFCA07-RG174-L300

Series:SMA Female-SMA Male R/A

Cable:RG174 Cable or RG316 Cable

Lengs:L300=300mm

No.	Name	Description	UNITS	QTY
1	Connetor	SMA Plug, Male Right angle, for RG174 or RG316	PCS	1
2	Heat-Shrink Tube	∅2.5mm Heat-Shrink Tube, Black, L15mm	PCS	2
3	RF Cable	RG174 Cable, Black, ∅∅2.7mm	mm	L
4	Connector	SMA Jack, Female Straight, for RG174, with CAP(Red)	PCS	1
5	Washers	T0.4mm Washers	PCS	1
6	Nut	T1.8mm Nut, 1/4 36UNS-2A	PCS	1

	NINGBO RHT ELECTRONIC CO.,LTD				UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN	SMA Female to SMA Male R/A Cable		
					0~3	3~18	18~50	50~120	CHK'D BY FENG	THIRD ANGLE PROJECTION 	RHTAYFCA07-XXXX
					±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN		