

Note:

- 1: V.S.W.R: 1.5(0~3G), Max.
- 2: Wire surface shall have no dirt, broken.
- 3: Connector surface with coating, oxidation phenomenon.
- 4: Connector pins and insulator are in the same plane

Order Information

RHTAYFCA11-DD1.13-L300/X

- Series: I-PEX to SMA plug, Male
- Cable: DD0.81-0.81mm RF Cable
- DD1.13-1.13mm RF Cable
- DD1.32-1.32mm RF Cable
- DD1.37-1.37mm RF Cable
- RG178-RG178 RF Cable
- DD316-RG316 RF Cable
- Lengs: L300=300mm
- Wire Color: Not-Black
- G-Gray BR-Brown


No.	Name	Description	UNITS	QTY
1	Connetor	I-PEX Plug,for RG178,RG316,0.81,1.13,1.32,1.37mm Cable	PCS	1
2	Heat-Shrink Tube	∅1.0mm Heat-Shrink Tube,Black,L15mm	PCS	2
3	RF Cable	RG178,RG316,0.81,1.13,1.32,1.37mm Cable	mm	L
4	Connector	SMA plug,Male Straight,for RG178,RG316,0.81,1.13,1.32,1.37mm	PCS	1

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5

CHK'D BY FENG
APPR BY ZHAN

I-PEX to SMA Male Cable



RHTAYFCA11-XXXX