

Note:

1:V.S.W.R:1.5(0~3G),Max.

2:Wire surface shall have no dirt,broken.

3:Connector surface with coating,oxidation phenomenon.

4:Connector pins and insulator are in the same plane

Order Information

RHTAYFCA12-RG316-L300


Series:MCX plug, Male-MCX jack, Female

Cable:RG316 or RG178

Lengs:L300=300mm

No.	Name	Description	UNITS	QTY
1	Connetor	MCX plug, Male Straight, for RG316 or RG178 Cable	PCS	1
2	Heat-Shrink Tube	∅2.5mm Heat-Shrink Tube, Black, L15mm	PCS	2
3	RF Cable	RG316 or RG178 Cable	mm	L
4	Connector	MCX Jack, Female Straight for RG316 or RG178 Cable	PCS	1
5	Washers	T0.5mm Washers	PCS	1
6	Nut	T1.5mm Nut, 10 56UNS-2A	PCS	1

 NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4		SCALE:---		DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	THIRD ANGLE PROJECTION 
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	

MCX plug to MCX Jack Cable

RHTAYFCA12-XXXX