

Note:

- 1: V.S.W.R: 1.5(0~3G), Max.
- 2: Wire surface shall have no dirt, broken.
- 3: Connector surface with coating, oxidation phenomenon.
- 4: Connector pins and insulator are in the same plane

Order Information

RHTAYFCA13-RG316-L300

Series: _____

MCX plug, Male R/A-MCX Jack, Female

Cable: RG316 or RG178 _____

Length: L300=300mm _____

No.	Name	Description	UNITS	QTY
1	Connector	MCX plug, Male Right Angle, for RG316 or RG178 Cable	PCS	1
2	Heat-Shrink Tube	∅2.5mm Heat-Shrink Tube, Black, L15mm	PCS	2
3	RF Cable	RG316 or RG178 Cable	mm	L
4	Connector	MCX Jack, Female Straight for RG316 or RG178 Cable	PCS	1
5	Washers	T0.5mm Washers	PCS	1
6	Nut	T1.5mm Nut, 10 56UNS-2A	PCS	1

 NINGBO RHT ELECTRONIC CO., LTD

UNITS:mm	SHEET SIZE: A4		SCALE: ---	
0~3	3~18	18~50	50~120	
±0.12	±0.15	±0.3	±0.5	


DRWN BY PAN

CHK'D BY FENG

APPR BY ZHAN

MCX plug R/A to MCX Jack Cable

THIRD ANGLE PROJECTION



RHTAYFCA13-XXXX