

Dimensions : Millimetres

Item	Description
1	SMA B/H Jack Crimp Type for $\phi 1.37$ mm Cable (Nut $\times 1$,Washer $\times 1$)
2	Heat Shrink Tube F32 $\phi 2.5$ mm L=10mm Colour:Black
3	$\phi 1.37$ mm Cable Colour:Black
4	U.FL-LP-088 Shell for $\phi 1.37$ mm Cable
5	U.FL-LP-088 Terminal for $\phi 1.37$ mm Cable

Specifications:

Connector Type A:U.FL

Connector Type B:SMA

Impedance:50 Ω

Frequency Range:DC to 3GHz

Maximum Working Voltage:60V rms

Min. Dielectric Withstanding Voltage:200V rms

Min. Insulation Resistance:500M Ω

Cable Assembly Type:RF Coaxial

Cable Length:200mm

External Diameter:1.37mm

Cable Colour:Black

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4			SCALE:---
0~3	3~18	18~50	50~120	
± 0.12	± 0.15	± 0.3	± 0.5	


DRWN BY PAN

CHK'D BY FENG

APPR BY ZHAN

MULTICOMP PRO R-132G7210200CB RRF
Cable,U.FL-SMA, IP67, L200mm Cross

THIRD ANGLE PROJECTION



RHTAYFCA06A-0D1.13-L200