



Note:

- 1:V.S.W.R:1.5(0~3G),Max.
- 2:Wire surface shall have no dirt,broken.
- 3:Connector surface with coating,oxidation phenomenon.
- 4:Connector pins and insulator are in the same plane

Order Information

RHTAYFCA22-RG174-L300

Series:MMCX Male R/A

to MMCX Male R/A

Cable:RG174 Cable or RG316 Cable

Lengs: L300=300mm

No.	Name	Description	UNITS	QTY
1	Connetor	MMCX Male Plug,Right angle,for RG174 or RG316	PCS	1
2	Heat-Shrink Tube	∅2.5mm Heat-Shrink Tube,Black,L15mm	PCS	2
3	RF Cable	RG174 Cable, Black,∅2.7mm	mm	L
4	Connector	MMCX Male Plug,Right angle,for RG174 or RG316	PCS	1

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5

CHK'D BY FENG
APPR BY ZHAN

MMCX Male R/A to MMCX Male R/A Cable
THIRD ANGLE PROJECTION
RHTAYFCA22-XXXX