



Note:

- 1:V.S.W.R:1.5(0~3G),Max.
- 2:Wire surface shall have no dirt,broken.
- 3:Connector surface with coating,oxidation phenomenon.
- 4:Connector pins and insulator are in the same plane

Order Information

RHTAYFCA25-RG58-L300

Series:RP SMA Male-N Male

Cable:RG58 Cable

Length:L300=300mm

| No. | Name             | Description                         | UNITS | QTY |
|-----|------------------|-------------------------------------|-------|-----|
| 1   | Connetor         | RP SMA Plug,Male Straight,for RG58  | PCS   | 1   |
| 2   | Heat-Shrink Tube | ∅5.0mm Heat-Shrink Tube,Black,L20mm | PCS   | 2   |
| 3   | RF Cable         | RG58 Cable, Black,∅5.0mm            | mm    | L   |
| 4   | Connector        | N-J,Male ,for RG58                  | PCS   | 1   |

**RHTECP** NINGBO RHT ELECTRONIC CO.,LTD

|          |                |       |           |               |
|----------|----------------|-------|-----------|---------------|
| UNITS:mm | SHEET SIZE: A4 |       | SCALE:--- | DRWN BY PAN   |
| 0~3      | 3~18           | 18~50 | 50~120    | CHK'D BY FENG |
| ±0.12    | ±0.15          | ±0.3  | ±0.5      | APPR BY ZHAN  |

SMA Male to N Male Cable

THIRD ANGLE PROJECTION



RHTAYFCA25-XXXX