



Note:

- 1:V.S.W.R:1.5(0~3G),Max.
- 2:Wire surface shall have no dirt,broken.
- 3:Connector surface with coating,oxidation phenomenon.
- 4:Connector pins and insulator are in the same plane

Order Information

RHTAYFCA26-RG174-L300

Series:SMA plug, _____
 Male-RP SMA plug, Male
 Cable:RG174 Cable or RG316 Cable _____
 Lengs: L300=300mm _____

No.	Name	Description	UNITS	QTY
1	Connetor	SMA Plug, Male Straight, for RG174	PCS	1
2	Heat-Shrink Tube	∅2.5mm Heat-Shrink Tube, Black, L15mm	PCS	2
3	RF Cable	RG174 Cable, Black, ∅2.7mm	mm	L
4	Connector	RP SMA , Male for RG174	PCS	1

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5

CHK'D BY FENG
APPR BY ZHAN

SMA Male to RP SMA Male Cable
THIRD ANGLE PROJECTION
RHTAYFCA26-XXXX