

Note:

- 1:V.S.W.R:1.5(0~3G),Max.
- 2:Wire surface shall have no dirt,broken.
- 3:Connector surface with coating,oxidation phenomenon.
- 4:Connector pins and insulator are in the same plane

Order Information


RHTAYFCA28-RG316-L300

Series:SMA Plug, _____
 Male-R/A SMA Plug, Male R/A
 Cable:RG316 Cable _____
 Lengs:L300=300mm _____

No.	Name	Description	UNITS	QTY
1	Connetor	SMA plug, Male Right angle, for RG316	PCS	1
2	Heat-Shrink Tube	Ø2.5mm Heat-Shrink Tube, Black, L15mm	PCS	2
3	RF Cable	RG316 Cable, Brown, Ø2.5mm	mm	L
4	Connector	SMA plug, Male Right angle, for RG316	PCS	1

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4				SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	SMA Male R/A to SMA Male R/A Cable	
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	THIRD ANGLE PROJECTION	



RHTAYFCA28-XXXX