

Note:

- 1:V.S.W.R:1.5(0~3G),Max.
- 2:Wire surface shall have no dirt,broken.
- 3:Connector surface with coating,oxidation phenomenon.
- 4:Connector pins and insulator are in the same plane

Order Information

RHTAYFCA29-RG174-L300

Series:MCX plug, Male Straight to SMA Female  
 Cable:RG174 Cable or RG316 Cable  
 Lengs:L300=300mm


No.	Name	Description	UNITS	QTY
1	Connetor	MCX Plug Male Straight,for RG174 or RG316	PCS	1
2	Heat-Shrink Tube	∅2.5mm Heat-Shrink Tube,Black,L15mm	PCS	2
3	RF Cable	RG174 Cable, Black,∅∅2.7mm	mm	L
4	Connector	SMA Jack,Female Straight,for RG174,with CAP(Red)	PCS	1
5	Washers	T0.4mm Washers	PCS	1
6	Nut	T1.8mm Nut,1/4 36UNS-2A	PCS	1

 NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4		SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN

MCX plug, Male Straight to SMA Female Cable

THIRD ANGLE PROJECTION



RHTAYFCA29-XXXX