

Note:

- 1:V.S.W.R:1.5(0~3G),Max.
- 2:Wire surface shall have no dirt,broken.
- 3:Connector surface with coating,oxidation phenomenon.
- 4:Connector pins and insulator are in the same plane

Order Information

RHTAYFCA32-RG316-L300

Series:SMB Plug, _____
 Female-to SMB Plug,Female R/A _____
 Cable:RG316 or RG178 _____
 Lengs:L300=300mm _____

No.	Name	Description	UNITS	QTY
1	Connetor	SMB plug,Female Right ,for RG316/RG174	PCS	1
2	Heat-Shrink Tube	∅2.5mm Heat-Shrink Tube,Black,L15mm	PCS	2
3	RF Cable	RRG316 or RG178 Cable	mm	L
4	Connector	SMB plug,Female Right angle,for RG316/RG174	PCS	1

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4		SCALE:---
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5


DRWN BY PAN

CHK'D BY FENG

APPR BY ZHAN

SMB plug,Female to SMB plug,Female R/A Cable

THIRD ANGLE PROJECTION



RHTAYFCA32-XXXX